

# Purely the best in the business! Endot EndoPure®!

- Lifetime warranty.
- 100% virgin resin.
- Consecutive footage marks.
- Quality • Reliability • Consistency.

ENDOT ENDOPURE  
25 FEET

ENDOT ENDOPURE  
26 FEET

We do our  
best work  
under  
pressure!

A family-owned  
business celebrating  
40 years  
of service.

Nationwide!

Available through distributors nationwide;  
call for the one nearest you.



Endot Industries, Inc., 60 Green Pond Road, Rockaway, NJ 07866  
<http://www.endot.com> • e-mail: [info@endot.com](mailto:info@endot.com)

1-800-44-ENDOT



# EndoPure

*The ONLY High Density Polyethylene Pipe specially engineered for the water industry.*

ENDOT EndoPure. On the outside, it's blue, color coded for the coming industry standard; on the inside it's completely natural; overall it's the purest polyethylene, so it's: Lead Free, Chlorine Free and Solvent Free. EndoPure comes ENDOT sealed with our special crimping process to ensure that it remains impurity free. Guaranteed. For your next project, make it ENDOT'S EndoPure . . . and make it as perfect as possible.

ENDOT Industries backs EndoPure with a certificate of purity in addition to a lifetime Warranty, including the most liberal cost of replacement provisions. (See Warranty for Details)

## APPLICABLE STANDARDS (MATERIAL & DIMENSIONAL)

ENDOT EndoPure meets the specifications of NSF-14 & 61, AWWA C901-08 plus the following standards:

### Material Standards PE 4710

ASTM D3350 - Cell Classification	
UV Stabilized Clear Center -	445576D
UV Stabilized Blue Exterior -	445576E
ASTM D1505 - Density	.949 g/cc
ASTM D1238 - Melt Index	>0.08 g/10 min
ASTM D638 - Tensile Strength	>3600psi
ASTM D638 - Elongation	>740%
ASTM D2837 - Hydrostatic Design Basis	1600psi @ 20°C
ASTM D790 - Flexural Modulus	150,000psi
ASTM D746 - Brittleness Temp.	<-103°F
ASTM D1693 - Slow Crack Growth Pent	>25,000 hours

### Dimensional Standards

ASTM D2239 - SIDR - Iron Pipe Size (IPS), Controlled Inside Diameter  
ASTM D2737 - SODR - Copper Tube Size (CTS), Controlled Outside Diameter  
ASTM D3035 - DR - Iron Pipe Size (IPS), Controlled Outside Diameter

Also available in lavender for reclaimed water and green for sewer applications.

For your next project, make it EndoPure . . . and make it as pure as possible!

For the latest information on products and services,  
visit:

[www.endot.com](http://www.endot.com)

e-mail:

[info@endot.com](mailto:info@endot.com)

#### CORPORATE HEADQUARTERS

60 Green Pond Road  
Rockaway, NJ 07866  
800-443-6368 • FAX 973-625-4087



#### ENDOT INDUSTRIES, INC.

[www.endot.com](http://www.endot.com) • e-mail: [info@endot.com](mailto:info@endot.com)



#### PLANT LOCATIONS

Greeneville, TN  
Pryor Creek, OK